

# EXHIBIT C

```
0 /* *****
1   File: sslrec.c
2
3   SSL Plus: Security Integration Suite(tm)
4   Version 1.1.1 -- August 11, 1997
5
6   Copyright (c)1996, 1997 by Consensus Development Corporation
7   Copyright (c)1997, 1998 by Aventail Corporation
8
9   Portions of this software are based on SSLRef(tm) 3.0, which is
10  Copyright (c)1996 by Netscape Communications Corporation. SSLRef(tm)
11  was developed by Netscape Communications Corporation and Consensus
12  Development Corporation.
13
14  In order to obtain this software, your company must have signed
15  either a PRODUCT EVALUATION LICENSE (a copy of which is included in
16  the file "LICENSE.TXT"), or a PRODUCT DEVELOPMENT LICENSE. These
17  licenses have different limitations regarding how you are allowed to
18  use the software. Before retrieving (or using) this software, you
19  *must* ascertain which of these licenses your company currently
20  holds. Then, by retrieving (or using) this software you agree to
21  abide by the particular terms of that license. If you do not agree
22  to abide by the particular terms of that license, than you must
23  immediately delete this software. If your company does not have a
24  signed license of either kind, then you must either contact
25  Consensus Development and execute a valid license before retrieving
26  (or using) this software, or immediately delete this software.
27
28  *****
29
30  File: sslrec.c      Encryption, decryption and MACing of data
31
32  All the transformations which occur between plaintext and the
33  secured, authenticated data that goes out over the wire. Also,
34  detects incoming SSL 2 hello messages and hands them off to the SSL 2
35  record layer (and hands all SSL 2 reading & writing off to the SSL 2
36  layer).
37
38  ***** */
39
40 /* #define HYPER_DEBUG 1 */
41
42 #ifdef HYPER_DEBUG
43 #include <stdio.h>
44 #endif
45
46 #ifndef _SSL_H_
47 #include "ssl.h"
48 #endif
49
50 #ifndef _SSLREC_H_
51 #include "sslrec.h"
52 #endif
53
54 #ifndef _SSLALLOC_H_
55 #include "sslalloc.h"
56 #endif
57
58 #ifndef _CRYPTYPE_H_
59 #include "cryptype.h"
60 #endif
61
62 #ifndef _SSLCTX_H_
63 #include "sslctx.h"
64 #endif
65
66 #ifndef _SSLALERT_H_
67 #include "sslalert.h"
68 #endif
69
70 #ifndef _SSL2_H_
```

```
71 #include "ssl2.h"
72 #endif
73
74 #include <string.h>
75
76 static SSLerr DecryptSSLRecord(uint8 type, SSLBuffer *payload, SSLContext *ctx);
77 static SSLerr VerifyMAC(uint8 type, SSLBuffer data, uint8 *compareMAC, uint64 seqNo, SSLContext
    *ctx);
78 static SSLerr ComputeMAC(uint8 type, SSLBuffer data, SSLBuffer mac, uint64 seqNo, SSLBuffer
    secret, CipherContext *cipherCtx, SSLContext *ctx);
79 static uint8* SSLEncodeUInt64(uint8 *p, uint64 value);
80
81 /* ReadSSLRecord
82  * Attempt to read & decrypt an SSL record.
83  */
84 SSLerr
85 SSLReadRecord(SSLRecord *rec, SSLContext *ctx)
86 {
87     SSLerr      err;
88     uint32      len, contentLen;
89     uint8       *progress;
90     SSLBuffer    readData, cipherFragment;
91
92 #ifdef HYPER_DEBUG
93     fprintf(stderr, "Got into SSLReadRecord, whee!\n");
94 #endif
95
96     /* if we get UDP data when we aren't expecting it, that's really bad,
97      so report an appropriate error. */
98     if((rec->contentType == SSL_application_data_ssloppy) &&
99         (! ctx->ssloppy))
100         return SSLProtocolErr;
101
102
103     if (!ctx->partialReadBuffer.data || ctx->partialReadBuffer.length < 5)
104     {
105         if (ctx->partialReadBuffer.data)
106             if ((err = SSLFreeBuffer(&ctx->partialReadBuffer, &ctx->sysCtx)) != 0)
107                 {
108                     SSLFatalSessionAlert(alert_close_notify, ctx);
109                     return ERR(err);
110                 }
111         if ((err = SSLAllocBuffer(&ctx->partialReadBuffer, DEFAULT_BUFFER_SIZE, &ctx->sysCtx))
112             != 0)
113             {
114                 SSLFatalSessionAlert(alert_close_notify, ctx);
115                 return ERR(err);
116             }
117     }
118
119     if (ctx->protocolVersion == SSL_Version_Undetermined ||
120         ctx->protocolVersion == SSL_Version_3_0_With_2_0_Hello)
121     {
122         if (ctx->amountRead < 1)
123         {
124             readData.length = 1 - ctx->amountRead;
125             readData.data = ctx->partialReadBuffer.data + ctx->amountRead;
126             len = readData.length;
127             if (ERR(err = ctx->ioCtx.read(readData, &len, ctx->ioCtx.ioRef)) != 0)
128             {
129                 if (err == SSLWouldBlockErr)
130                     ctx->amountRead += len;
131                 else
132                     SSLFatalSessionAlert(alert_close_notify, ctx);
133                 return err;
134             }
135             ctx->amountRead += len;
136         }
137     }
138
139     /* In undetermined cases, if the first byte isn't in the range of SSL 3.0
140     * record types, this is an SSL 2.0 record
141     */
142     switch (ctx->protocolVersion)
143     {
144         case SSL_Version_Undetermined:
145         case SSL_Version_3_0_With_2_0_Hello:
146             if (ctx->partialReadBuffer.data[0] < SSL_smallest_3_0_type ||
147                 ctx->partialReadBuffer.data[0] > SSL_largest_3_0_type)
```

```
139         return SSL2ReadRecord(rec, ctx);
140     else
141         break;
142     case SSL_Version_2_0:
143         return SSL2ReadRecord(rec, ctx);
144     default:
145         break;
146 }
147
148
149 #ifdef HYPER_DEBUG
150     fprintf(stderr, "About to get into the read callback stuff\n");
151 #endif
152     if (ctx->amountRead < 5)
153     {
154         readData.length = 5 - ctx->amountRead;
155         readData.data = ctx->partialReadBuffer.data + ctx->amountRead;
156         len = readData.length;
157         if (ERR(err = ctx->ioCtx.read(readData, &len, ctx->ioCtx.ioRef)) != 0)
158         {
159             if (err == SSLWouldBlockErr)
160                 ctx->amountRead += len;
161             else if (err == SSLIOClosedOverrideGoodbyeKiss && ctx->amountRead ==
162 0)
163             {
164                 SSLClose(ctx);
165                 return SSLConnectionClosedGraceful;
166             }
167             else
168                 SSLFatalSessionAlert(alert_close_notify, ctx);
169             return err;
170         }
171         ctx->amountRead += len;
172     }
173     ASSERT(ctx->amountRead >= 5);
174     progress = ctx->partialReadBuffer.data;
175     rec->contentType = *progress++;
176     if (rec->contentType < SSL_smallest_3_0_type ||
177         rec->contentType > SSL_largest_3_0_type)
178         return ERR(SSLProtocolErr);
179     rec->protocolVersion = (SSLProtocolVersion)SSLDecodeInt(progress, 2);
180     progress += 2;
181     contentLen = SSLDecodeInt(progress, 2);
182     progress += 2;
183     if (contentLen > (16384 + 2048)) /* Maximum legal length of an SSLCipherText payload */
184     {
185         SSLFatalSessionAlert(alert_unexpected_message, ctx);
186         return ERR(SSLProtocolErr);
187     }
188     if (ctx->partialReadBuffer.length < 5 + contentLen)
189     {
190         if ((err = SSLReallocBuffer(&ctx->partialReadBuffer, 5 + contentLen, &ctx->sysCtx)) !=
191 0)
192         {
193             SSLFatalSessionAlert(alert_close_notify, ctx);
194             return ERR(err);
195         }
196     }
197     if (ctx->amountRead < 5 + contentLen)
198     {
199         readData.length = 5 + contentLen - ctx->amountRead;
200         readData.data = ctx->partialReadBuffer.data + ctx->amountRead;
201         len = readData.length;
202         if (ERR(err = ctx->ioCtx.read(readData, &len, ctx->ioCtx.ioRef)) != 0)
203         {
204             if (err == SSLWouldBlockErr)
205                 ctx->amountRead += len;
206             else
207                 SSLFatalSessionAlert(alert_close_notify, ctx);
208             return err;
209         }
210         ctx->amountRead += len;
211     }
212 }
```

```
208     ASSERT(ctx->amountRead >= 5 + contentLen);
209
210     cipherFragment.data = ctx->partialReadBuffer.data + 5;
211     cipherFragment.length = contentLen;
212
213     /* Decrypt the payload & check the MAC, modifying the length of the buffer to indicate the
214      * amount of plaintext data after adjusting for the block size and removing the MAC
215      * (this function generates its own alerts)
216      */
217     if ((err = DecryptSSLRecord(rec->contentType, &cipherFragment, ctx)) != 0)
218         return err;
219
220     /* We appear to have successfully received a record; increment the sequence number */
221     if (rec->contentType != SSL_application_data_sslappy)
222         IncrementUInt64(&ctx->readCipher.sequenceNum);
223
224
225 #ifdef SSL_COMPRESSION
226     if ((ctx->compressNow) && (ctx->selectedCompression != NULL) &&
227         (ctx->selectedCompression->identifier != 0)) {
228
229         /* Allocate a buffer to return the plaintext in and return it */
230         if ((err = SSLAllocBuffer(&rec->contents, DEFAULT_BUFFER_SIZE,
231             &ctx->sysCtx)) != SSLNoErr) {
232             SSLFatalSessionAlert(alert_close_notify, ctx);
233             return ERR(err);
234         }
235         if ((err = ctx->selectedCompression->process(cipherFragment,
236             &(rec->contents),
237
238             ctx->readCompressRef,
239
240             ctx)) != SSLNoErr) {
241             SSLFreeBuffer(&rec->contents, &ctx->sysCtx);
242             SSLFatalSessionAlert(alert_decompression_failure, ctx);
243             return ERR(err);
244         }
245         #ifdef HYPER_DEBUG
246             fprintf(stderr, "Decompression created output of %d from size %d\n",
247                 cipherFragment.length,
248                 rec->contents.length);
249         #endif
250         } else {
251             if ((err = SSLAllocBuffer(&rec->contents, cipherFragment.length,
252                 &ctx->sysCtx)) != 0)
253             {
254                 SSLFatalSessionAlert(alert_close_notify, ctx);
255                 return ERR(err);
256             }
257             memcpy(rec->contents.data, cipherFragment.data, (size_t)
258                 cipherFragment.length);
259         }
260     #else
261         memcpy(rec->contents.data, cipherFragment.data, (size_t) cipherFragment.length);
262     #endif
263
264     ctx->amountRead = 0;          /* We've used all the data in the cache */
265
266     return SSLNoErr;
267 }
268
269 /* SSLWriteRecord does not send alerts on failure, out of the assumption/fear
270 * that this might result in a loop (since sending an alert causes SSLWriteRecord
271 * to be called).
272 */
```

```
269 SSLerr
270 SSLWriteRecord(SSLRecord rec, SSLContext *ctx)
271 {   SSLerr      err;
272     int          padding = 0, i, freerec = 0;
273     WaitingRecord *out, *queue;
274     SSLBuffer      buf, payload, secret, mac, nonce;
275     uint8          *progress;
276     uint16         payloadSize, blockSize, nonceSize = 0;
277
278     if (rec.protocolVersion == SSL_Version_2_0)
279         return SSL2WriteRecord(rec, ctx);
280
281     ASSERT(rec.protocolVersion == SSL_Version_3_0);
282     ASSERT(rec.contents.length <= 16384);
283
284 #ifdef SSL_COMPRESSION
285     if((ctx->compressNow) && (ctx->selectedCompression != NULL) &&
286         (ctx->selectedCompression->identifier != 0)) {
287         SSLBuffer compdata;
288
289         /* make a guess about how long the buffer will need to be */
290         if((err = SSLAllocBuffer(&compdata, rec.contents.length + 4,
291             &ctx->sysCtx)) != SSLNoErr)
292             return ERR(err);
293         if((err = ctx->selectedCompression->process(rec.contents, &compdata,
294             ctx->writeCompressRef,
295             ctx)) != SSLNoErr) {
296             SSLFreeBuffer(&compdata, &ctx->sysCtx);
297             return ERR(err);
298         }
299         rec.contents = compdata;
300         freerec = 1;
301     }
302 #endif
303
304     out = 0;
305     /* Allocate a WaitingRecord to store our ready-to-send record in */
306     if ((err = SSLAllocBuffer(&buf, sizeof(WaitingRecord), &ctx->sysCtx)) != 0)
307         return ERR(err);
308     out = (WaitingRecord*)buf.data;
309     out->next = 0;
310     out->sent = 0;
311
312     /* Allocate enough room for the transmitted record, which will be:
313      * 5 bytes of header +
314      * encrypted contents +
315      * macLength +
316      * padding [block ciphers only] +
317      * padding length field (1 byte) [block ciphers only]
318      */
319     payloadSize = (uint16) (rec.contents.length + ctx->writeCipher.hash->digestSize);
320     blockSize = ctx->writeCipher.symCipher->blockSize;
321     if (blockSize > 0)
322     {   padding = blockSize - (payloadSize % blockSize) - 1;
323         payloadSize = (uint16) (payloadSize + padding + 1);
324     }
325
326     if(ctx->ssloppy)
327     {
328         /* in this case we need more room, for the nonce */
329         nonceSize = (uint16) MAX(sizeof(uint64), ctx->writeCipher.symCipher->ivSize);
330         /* payloadSize += nonceSize; decided this was wrong logic */
331     }
332
333     out->data.data = 0;
```

Revision 1.6.10.1, by *marcvh*

```
334     if ((err = SSLAllocBuffer(&out->data, 5 + payloadSize + nonceSize,
335                               &ctx->sysCtx)) != 0)
336         goto fail;
337
338     progress = out->data.data;
339     *(progress++) = rec.contentType;
340     progress = SSLEncodeInt(progress, rec.protocolVersion, 2);
341     progress = SSLEncodeInt(progress, payloadSize, 2);
342
343     /* Copy the contents into the output buffer */
344     memcpy(progress, rec.contents.data, (size_t) rec.contents.length);
345     payload.data = progress;
346     payload.length = rec.contents.length;
347
348     progress += rec.contents.length;
349     /* MAC immediately follows data */
350     mac.data = progress;
351     mac.length = ctx->writeCipher.hash->digestSize;
352     progress += mac.length;
353
354     if (ctx->ssloppy)
355     {
356         uint64 noncevalue;
357
358         if ((err = SSLAllocBuffer(&nonce, nonceSize, &ctx->sysCtx)) != SSLNoErr)
359             goto fail;
360         if ((err = ctx->sysCtx.random(nonce, ctx->sysCtx.randomRef)) != SSLNoErr)
361             goto fail;
362
363         memcpy(&noncevalue, nonce.data, sizeof(noncevalue));
364
365         /* MAC the data, sloppy-style */
366         if (mac.length > 0) /* Optimize away null case */
367         {
368             secret.data = ctx->writeCipher.macSecret;
369             secret.length = ctx->writeCipher.hash->digestSize;
370             if ((err = ComputeMAC(rec.contentType, payload, mac, noncevalue,
371                                   secret, &ctx->writeCipher, ctx)) != 0)
372                 goto fail;
373         }
374
375         memcpy(progress, nonce.data, nonce.length);
376         progress += nonce.length;
377     }
378     else
379     {
380         /* MAC the data, normal mode */
381         if (mac.length > 0) /* Optimize away null case */
382         {
383             secret.data = ctx->writeCipher.macSecret;
384             secret.length = ctx->writeCipher.hash->digestSize;
385             if ((err = ComputeMAC(rec.contentType, payload, mac,
386                                   ctx->writeCipher.sequenceNum, secret,
387                                   &ctx->writeCipher, ctx)) != 0)
388                 goto fail;
389         }
390     }
391 }
392
393 /* Update payload to reflect encrypted data: contents, mac & padding */
394 payload.length = payloadSize;
395
396 /* Fill in the padding bytes & padding length field with the padding value; the
397  * protocol only requires the last byte,
398  * but filling them all in avoids leaking data
399  */
400 if (ctx->writeCipher.symCipher->blockSize > 0)
401     for (i = 1; i <= padding + 1; ++i)
402         payload.data[payload.length - i] = (uint8)padding;
403
404 /* Encrypt the data */
```

```
405     DUMP_BUFFER_NAME("cleartext data", payload);
406     if ((err = ctx->writeCipher.symCipher->encrypt(payload, payload,
407
                                                    ctx-
408
                                                    ctx-
409
                                                    ctx))
        != 0)
410         goto fail;
411
412     DUMP_BUFFER_NAME("encrypted data", payload);
413
414     /* Enqueue the record to be written from the idle loop */
415     if (ctx->recordWriteQueue == 0)
416         ctx->recordWriteQueue = out;
417     else
418     {
419         queue = ctx->recordWriteQueue;
420         while (queue->next != 0)
421             queue = queue->next;
422         queue->next = out;
423     }
424     if (ctx->ssloppy)
425         SSLFreeBuffer(&nonce, &ctx->sysCtx);
426     else
427         /* Increment the sequence number */
428         IncrementUInt64(&ctx->writeCipher.sequenceNum);
429
430     if (freerec)
431         SSLFreeBuffer(&(rec.contents), &ctx->sysCtx);
432
433     return SSLNoErr;
434
435 fail: /* Only for if we fail between when the WaitingRecord is allocated and when it is
        queued */
436     SSLFreeBuffer(&out->data, &ctx->sysCtx);
437     buf.data = (uint8*)out;
438     buf.length = sizeof(WaitingRecord);
439     SSLFreeBuffer(&buf, &ctx->sysCtx);
440     if (freerec)
441         SSLFreeBuffer(&(rec.contents), &ctx->sysCtx);
442     return ERR(err);
443 }
444
445 static SSLErr
446 DecryptSSLRecord(uint8 type, SSLBuffer *payload, SSLContext *ctx)
447 {
448     SSLErr err;
449     SSLBuffer content, nonce;
450
451     if (type == SSL_application_data_ssloppy)
452     {
453         nonce.length = MAX(sizeof(uint64), ctx->readCipher.symCipher->ivSize);
454         nonce.data = payload->data + (payload->length - nonce.length);
455         payload->length -= nonce.length;
456     }
457     if ((ctx->readCipher.symCipher->blockSize > 0) &&
458         ((payload->length % ctx->readCipher.symCipher->blockSize) != 0))
459     {
460         SSLFatalSessionAlert(alert_unexpected_message, ctx);
461         return ERR(SSLProtocolErr);
462     }
463     /* Decrypt in place */
464     DUMP_BUFFER_NAME("encrypted data", (*payload));
465
466     if (type == SSL_application_data_ssloppy)
467     {
468         if ((err = ctx->readCipher.symCipher->decrypt(*payload, *payload, &nonce, ctx-
469             >readCipher.symCipherState, ctx)) != 0)
469         {
```



```

470         SSLFatalSessionAlert(alert_close_notify, ctx);
471         return ERR(err);
472     }
473 }
474 else
475 {
476     if ((err = ctx->readCipher.symCipher->decrypt(*payload, *payload, NULL, ctx-
>readCipher.symCipherState, ctx)) != 0)
477     {
478         SSLFatalSessionAlert(alert_close_notify, ctx);
479         return ERR(err);
480     }
481     DUMP_BUFFER_NAME("decrypted data", (*payload));
482
483     /* Locate content within decrypted payload */
484     content.data = payload->data;
485     content.length = payload->length - ctx->readCipher.hash->digestSize;
486     if (ctx->readCipher.symCipher->blockSize > 0)
487     {
488         /* padding can't be equal to or more than a block */
489         if (payload->data[payload->length - 1] >= ctx->readCipher.symCipher->blockSize)
490         {
491             SSLFatalSessionAlert(alert_unexpected_message, ctx);
492             return ERR(SSLProtocolErr);
493         }
494         content.length -= 1 + payload->data[payload->length - 1]; /* Remove block size
padding */
495     }
496
497     /* Verify MAC on payload */
498     if (ctx->readCipher.hash->digestSize > 0) /* Optimize away MAC for null case */
499     {
500         if (type == SSL_application_data_ssloppy)
501         {
502             uint64 nonceNumber;
503
504             memcpy(&nonceNumber, nonce.data, sizeof(nonceNumber));
505             if ((err = VerifyMAC(type, content, payload->data + content.length,
nonceNumber, ctx)) != 0)
506             {
507                 SSLFatalSessionAlert(alert_bad_record_mac, ctx);
508                 return ERR(err);
509             }
510         }
511         else
512         {
513             if ((err = VerifyMAC(type, content, payload->data + content.length,
ctx->readCipher.sequenceNum, ctx)) !=
0)
514             {
515                 SSLFatalSessionAlert(alert_bad_record_mac, ctx);
516                 return ERR(err);
517             }
518         }
519     }
520
521     *payload = content; /* Modify payload buffer to indicate content length */
522     return SSLNoErr;
523 }
524
525 static uint8*
526 SSLEncodeUInt64(uint8 *p, uint64 value)
527 {
528     p = SSLEncodeInt(p, value.high, 4);
529     return SSLEncodeInt(p, value.low, 4);
530 }
531
532 static SSLerr
533 VerifyMAC(uint8 type, SSLBuffer data, uint8 *compareMAC, uint64 seqNo, SSLContext *ctx)
534 {
535     SSLerr err;
536     uint8 macData[MAX_DIGEST_SIZE];
537     SSLBuffer secret, mac;
538
539     secret.data = ctx->readCipher.macSecret;

```

```
538     secret.length = ctx->readCipher.hash->digestSize;
539     mac.data = macData;
540     mac.length = ctx->readCipher.hash->digestSize;
541
542     if ((err = ComputeMAC(type, data, mac, seqNo, secret,
543         &ctx->readCipher, ctx)) != 0)
544         return ERR(err);
545
546     if ((memcmp(mac.data, compareMAC, (size_t) mac.length)) != 0)
547         return ERR(SSLProtocolErr);
548
549     return SSLNoErr;
550 }
551
552 static SSLerr
553 ComputeMAC(uint8 type, SSLBuffer data, SSLBuffer mac, uint64 seqNo, SSLBuffer secret,
554     CipherContext *cipherCtx, SSLContext *ctx)
555 {
556     SSLerr      err;
557     uint8       innerDigestData[MAX_DIGEST_SIZE];
558     uint8       scratchData[11], *progress;
559     SSLBuffer    digest, scratch;
560
561 #ifdef HYPER_DEBUG
562     int i;
563     fprintf(stderr, "Buffer: ");
564     for(i = 0; i < data.length; i++)
565         fprintf(stderr, "%02x ", data.data[i]);
566     fprintf(stderr, "\n");
567     fprintf(stderr, "sequenceno: ");
568     for(i = 0; i < sizeof(uint64); i++)
569         fprintf(stderr, "%02x ", (unsigned char) *((unsigned char *) &seqNo) + i);
570     fprintf(stderr, "\n");
571     fprintf(stderr, "Secret: ");
572     for(i = 0; i < secret.length; i++)
573         fprintf(stderr, "%02x ", secret.data[i]);
574     fprintf(stderr, "\n");
575 #endif
576
577     ASSERT(cipherCtx->hash->macPadSize <= MAX_MAC_PADDING);
578     ASSERT(cipherCtx->hash->digestSize <= MAX_DIGEST_SIZE);
579     ASSERT(SSLMACPad1[0] == 0x36 && SSLMACPad2[0] == 0x5C);
580
581     if(cipherCtx->digestCtx.data == NULL) {
582         if ((err = SSLAllocBuffer(&cipherCtx->digestCtx,
583             cipherCtx->hash->contextSize, &ctx->sysCtx))
584             != 0)
585             goto exit;
586         cipherCtx->hash->create(cipherCtx->digestCtx);
587     }
588
589     /* MAC = hash( MAC_write_secret + pad_2 + hash( MAC_write_secret + pad_1 + seq_num + type +
590     length + content' ) ) */
591     if ((err = cipherCtx->hash->init(cipherCtx->digestCtx)) != 0)
592         goto exit;
593     if ((err = cipherCtx->hash->update(cipherCtx->digestCtx, secret)) != 0) /* MAC secret */
594         goto exit;
595     scratch.data = SSLMACPad1;
596     scratch.length = cipherCtx->hash->macPadSize;
597     if ((err = cipherCtx->hash->update(cipherCtx->digestCtx, scratch)) != 0) /* pad1 */
598         goto exit;
599     progress = scratchData;
600     progress = SSLEncodeUInt64(progress, seqNo);
601     *progress++ = type;
602     progress = SSLEncodeInt(progress, data.length, 2);
603     scratch.data = scratchData;
604     scratch.length = 11;
605     ASSERT(progress == scratchData+11);
606     if ((err = cipherCtx->hash->update(cipherCtx->digestCtx, scratch)) != 0) /* sequenceNo,
        type & length */
        goto exit;
```

```
607     goto exit;
608     if ((err = cipherCtx->hash->update(cipherCtx->digestCtx, data)) != 0) /* content */
609         goto exit;
610     digest.data = innerDigestData;
611     digest.length = cipherCtx->hash->digestSize;
612     if ((err = cipherCtx->hash->final(cipherCtx->digestCtx, digest)) != 0) /* figure inner
digest */
613         goto exit;
614
615     if ((err = cipherCtx->hash->init(cipherCtx->digestCtx)) != 0)
616         goto exit;
617     if ((err = cipherCtx->hash->update(cipherCtx->digestCtx, secret)) != 0) /* MAC secret */
618         goto exit;
619     scratch.data = SSLMACPad2;
620     scratch.length = cipherCtx->hash->macPadSize;
621     if ((err = cipherCtx->hash->update(cipherCtx->digestCtx, scratch)) != 0) /* pad2 */
622         goto exit;
623     if ((err = cipherCtx->hash->update(cipherCtx->digestCtx, digest)) != 0) /* inner digest
*/
624         goto exit;
625     if ((err = cipherCtx->hash->final(cipherCtx->digestCtx, mac)) != 0) /* figure the mac */
626         goto exit;
627
628     err = SSLNoErr; /* redundant, I know */
629
630 exit:
631     return ERR(err);
632 }
```